



LUNAprone WorldAxxcc TA200 Configuration



In the equipment configuration page:

Sip server information (Primary):

- Proxy server1 *216.206.188.214*port# *5070*
- Registration server1 *0.0.0.0*, port# *5070*
- Nat timer, Enable *empty*

Sip client information:

- User ID1 **LUNAprone PIN**
- Password **LUNAprone PASSWORD**
- Display name *any*
- Codec# *g729, g729A, g723, g711*
- All other settings *default*

WorldACCXX

TA-200

Unit Information WAN/LAN Configuration **SIP Configuration** Services Misc. Servers Maintenance

SIP Server Information (Primary)

Proxy Server 1:	<input type="text" value="216.206.188.200"/>	Port #: <input type="text" value="5070"/>	Enable: <input checked="" type="checkbox"/>
Registration Server 1:	<input type="text" value="0.0.0.0"/>	Port #: <input type="text" value="5070"/>	Interval(s): <input type="text" value="0"/>
NAT Timer (sec):	<input type="text" value="15"/>	Enable: <input type="checkbox"/>	

SIP Server Information (Secondary for Backup)

Proxy Server 2:	<input type="text" value="216.206.188.200"/>	Port #: <input type="text" value="5070"/>	Enable: <input checked="" type="checkbox"/>
Registration Server 2:	<input type="text" value="0.0.0.0"/>	Port #: <input type="text" value="5070"/>	Interval(s): <input type="text" value="0"/>
NAT Timer (sec):	<input type="text" value="15"/>	Enable: <input type="checkbox"/>	

SIP Client Information

Telephone #1 - Enable:

User ID 1: <input type="text" value="equip1"/>	Password: <input type="password" value="*****"/>	Display Name 1: <input type="text" value="Accxx1"/>
Authentication ID 1: <input type="text" value="Accxx1"/>	Enable: <input type="checkbox"/>	

Vocoder List Telephone 1

Codec # 1	Codec # 2	Codec # 3	Codec # 4
<input type="text" value="G.729"/>	<input type="text" value="G.729A"/>	<input type="text" value="G.723.1"/>	<input type="text" value="G.711/PCMU"/>

Fax Codec: T38 VBD Voice Frame per/IP Packet: 1-20 Default (4) Silence Sup.:

Media Port: 1024 to 65535 Default (27000)

Handset 1 Volume(speaker): Default 0 db(Med) Handset 1 Volume(mic): Default 0 db(Med)

Telephone #2 - Enable:

User ID 2: <input type="text" value="equip2"/>	Password: <input type="password" value="*****"/>	Display Name 2: <input type="text" value="Accxx2"/>
Authentication ID 2: <input type="text" value="Accxx2"/>	Enable: <input type="checkbox"/>	

Vocoder List Telephone 2

Codec # 1	Codec # 2	Codec # 3	Codec # 4
<input type="text" value="G.729"/>	<input type="text" value="G.729A"/>	<input type="text" value="G.723.1"/>	<input type="text" value="G.711/PCMU"/>

Fax Codec: T38 VBD Voice Frame per/IP Packet: 1-20 Default (4) Silence Sup.:

Media Port: 1024 to 65535 Default (27000)

Handset 2 Volume(speaker): Default 0 db(Med) Handset 2 Volume(mic): Default 0 db(Med)

WorldACCXX Telephone Adaptor V1.0
Copyright © 2004 WorldACCXX LLC, All Rights Reserved.

Notes

- If necessary DHCP, STUN servers are established in *WAN/LAN configuration* folder